



更改 REV	出图日期 DATE	设变内容 MODIFICATION	修改 DRAWN
	09/02/09		

**SPECIFICATIONS**

1. ELECTRICAL:  
 UL APPLICATIONS: 250 VOLTS AC MAX., AT 2 AMPS.  
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VOLTS AC.  
 INSULATION RESISTANCE: 100 MΩ.  
 TERMINATION: RESISTANCE 20mΩ MAX AFTER ENVIRONMENTAL TESTING.

2. MECHANICAL:  
 CABLE-TO-PLUG TENSILE STRENGTH: 20POUND MIN.  
 DURABILITY: 200 MATING CYCLES.

3. MATERIAL & FINISH:  
 HOUSING: POLYCARBONATE, UL94V-0 OR UL94V-2.  
 COLOR: TRANSPARENT OR OTHER COLOR ARE AVAILABLE.  
 CONTACT BLADE: COPPER ALLOY.  
 CONDUCTOR: STRANDED & SOLID WIRE, 24AWG, 26 AWG.  
 GOLD PLATING: 3u"-50u", ARE AVAILABLE.

**规范**

1. 电器:  
 UL应用最大250VOLTS AC.  
 介质耐压伏特数:500VOLTS AC.  
 绝缘阻抗:100百万欧姆.  
 终端阻抗:在环境测试后最大可承受20微欧姆终端阻抗.

2. 机构  
 拉力测试:至少20磅.  
 耐力测试:至少200次之插拔测试.

3. 材质表面处理  
 塑胶壳:聚碳酸脂,UL-94V-0 or UL94V-2.  
 颜色:透明,或者其他颜色亦可.  
 金片:铜合金.  
 导体:多股线&单股线,24AWG,26AWG.  
 镀金厚度:3u"-50u",皆可提供.

ITEM: \_\_\_\_\_

BLADE:	E	Y	Z	A	YL	ZL			
Drawing									
Mark			✓			✓			
GOLD PLATING	3Mu"	3u"	6u"	15u"	30u"	50u"	CABLE TYPE	ROUND	FLAT
Mark					✓		Mark	✓	



客户用产品图

<b>EXW</b> 宁波卓新通讯接插件有限公司 NINGBO EXCELLENCE COMMUNICATED CONNECTOR CO.,LTD		材 质 MATERIAL	图 号 DWG NO.
DIMENSION IN mm (Inch) TOLERANCE UNLESS OTHERWISE SPECIFIED		PC	PLUG-053
.X±0.20	.X°±5°	名 称 TITLE	
.XX±0.10	.XX°±2°	P88R5Z50V21T	
审 核 APPROVAL	核 对 CHECKED	制 图 DRAWN	比 例 SCALE
沈红波	吴明	Lucia	5/2
		角 法 PROJ.	张 数 SHEET
			1/1
			更 改 REV
			J

ST-DR-009A