

Empty Patch Panel for 24 Snap-in Connectors

Patch Panel 24 Snap-In Fixed Black

Contactpersoon
Cabling Solutions
Telefoon: +32 2 363 38 00
info.ncs@nexans.com

Nexans ref.: [N521.661BK](#)

- Compatible with all LANmark Snap-In connectors
- 24 Snap-In ports with shutters
- Clip-on mechanism
- Exclusive Auto-Connect Earthing system
- Universal design supporting Unscreened and Screened connectors
- Also available in white

BESCHRIJVING

Nexans Snap-In range of patch panels are designed to accommodate any of the Snap-In connectors in the LANmark product family (LANmark-7A, LANmark-7, LANmark-6A, LANmark-6, and LANmark-5).

The Snap-In panels feature an exclusive Clip-On system to secure the connector in the panel and to provide a simple means of earthing shielded connectors to facilitate installation. Connection of the panel to earth is achieved with a unique Auto-Connect feature removing the need for individual bonding conductors.

The panels also have a series of complementary cable management products such as blank panels and patch cord guides.

The patch panels are designed for standard 19" enclosures, are 1U high, and support the following common features:

- 24 Ports with shutters
- Designed for Screened and Unscreened Snap-In connectors
- Compatible with all performance categories of connector
- Clip-On mechanism for simple earthing
- Exclusive rear cable management facilities
- Robust construction
- Printed numbering for port labelling

This panel features vertical "T" clips for rapid cable retention which allows loading of the panel in around 25% of the time needed to fasten tie wraps which leads to time saving during installation.



LANmark

NORMEN

Internationaal ISO/IEC 11801

Empty Patch Panel for 24 Snap-in Connectors

Patch Panel 24 Snap-In Fixed Black

Contactpersoon
Cabling Solutions
Telefoon: +32 2 363 38 00
info.ncs@nexans.com

KARAKTERISTIEKEN

Constructiekenmerken

Kleur	Zwart
Materiaal	Staal

Maatvoeringskenmerken

Eenheid van hoogte	1 U
Diepte	75 mm
Benaderend gewicht per stuk	0,65 kg
Breedte (in)	19 in

Gebruikskarakteristieken

Toepassingsgebied	Vaste installaties
Trillingsweerstand	Hoog
Mechanical Resistance	Good mechanical resistance
Aantal poorten	24
Verpakking	Box